



DEMO Design Activity in Europe: Progress and Updates

Gianfranco Federici, the PPPT PMU and Project Teams

Power Plant Physics and Technology



This work has been carried out within the framework of the EUROfusion Consortium and has received funding from the Euratom research and training programme 2014-2018 under grant agreement No 633053. The views and opinions expressed herein do not necessarily reflect those of the European Commission.




- ✓ **DEMO in the EU Roadmap**
- ✓ **Design Choices under Considerations**
- ✓ **Highlights of Technical Achievements**
- ✓ **Industry and International Collaborations**
- ✓ **Conclusions**



DEMO in the EU Fusion Roadmap



- An ambitious roadmap implemented since 2014 by a Consortium (EUROfusion) of 30 Fusion Labs from 26 EU member states (+ Switzerland and Ukraine) and F4E
- 33 Work Packages of different character including:
 - EU ITER physics coordination
 - Experimental campaigns JET & MSTs and PEX upgrade of devices
 - DEMO Concept Design (consisting of 13 WPs)
 - Education and Training and Enabling Research



Emphasis on:

- ❖ Central role of ITER **initial assumption FP 2020**
- ❖ DEMO Concept Design

High Level Requirements agreed with DEMO External Stakeholders (e.g., industry, utilities, grids, safety, licensing, funding bodies)

EU DEMO Mission requirements

- DEMO Net electricity (~500 MWe)
- Makes its own fuel (TBR > 1)
- Reliable operation
- Reasonable availability
- Allow extrapolation to a FPP


DEMO in the EU Fusion Roadmap (cont'd)



Revision triggered by:

- ❖ ITER delay: develop a strategy to minimise impact on mission to realise fusion electricity by ~2050's
- ❖ Underestimate of the “design integration” challenge
- ❖ Recommendations to explore a wider DEMO design space

Three phases: (1) a pre-concept design phase to be concluded in 2020; (2) a concept design phase with a CDR in 2027; and (3) an engineering design to follow.



Key Messages



- Contacts made with **Gen IV fission and ITER to learn from their experience.**
- **Definition of DEMO HLRs** following interaction with **external stakeholder group** composed of experts from industry, utilities, grids, safety, licensing, etc.
- A **philosophy of integrated design** established with a **traceable decision making process.**
- A **more systems-oriented approach** brought clarity to a number of critical design issues.
- Main **design Integration Risks** that affect Plant architecture identified.
- **Readiness of physics and technology assumptions of DEMO design points** by using **systems codes.**
- Sensitivities studies to **determine impact of uncertainties** of underlying physics and engineering/technology assumptions on machine parameters.
- **Design of a first DEMO plant layout** in collaboration with AREVA GmbH to identify major structures needed to contain the plant equipment; to identify needs for improvements.
- Preliminary **safety assessments**, including **assessments of radioactive waste.**
- **Evaluate multiple design options** for systems and/or technologies with high technical risk or novelty.


Current DEMO Design Baseline



Physics:

- Single null
- Conventional H-mode
- H=1.1 (radiation corrected)
- Based on ITER performance (Q=10)
- $P_{sep}/R_0=17$ MW/m (fully detached)
- Pulsed (2 hours)
- "Conservative", i.e. established physics basis.

H-mode access limit





	DEMO1
R_0	~9 m
A	3.1
k_{95}	1.65
B_T	4.9 T
β_N	2.6
H	1.1

$P_{el,net} = 500$ MW
 $\tau_{pulse} = 2$ hr
 $A = 3.1$



Engineering:

- 16 LTSC TF Coils, Nb_3Sn , ~12 T
- Vertical Maintenance
- EUROFER IVCs
- Starter blanket (20 dpa) + Second blanket (50 dpa) (~6-7 FPY total)
- TBR > 1.1
- Availability target 30%






Evaluate Multiple Design Options



PCS: Indirect (ESS)/ Direct



Flexi-DEMO

	Lower OP	Upper OP
R (m)	< 8.4	< 8.4
P_{el} (MW)	300	300
τ (hr)	1	St. State
q_{95}/β_N	4.8/3.3	4.2/2.9
H	1	1.2

Initially operate in a short pulse mode (e.g., 1 hr, but could move to steady-state operation with improvement of physics and CD.)

Legend: EU DEMO1 2017 (blue), Flexi DEMO (red)



Highlights of Technology Achievements

WPMAG - LTS TF cables


Wind & React



$\Delta T_{\text{marg}} > 2\text{K}$ @ 82kA, 13T
NO degradation with e-m cycles


- $\epsilon_{\text{eff}} \in [-0.55, -0.35]\%$
- Higher I_c
- Less SC strands

React & Wind




$\Delta T_{\text{marg}} > 2.0\text{K}$ $\epsilon_{\text{eff}} \approx -0.35\%$
Low degradation w. e-m cycles **Low AC losses**

$\Delta T_{\text{marg}} > 1.5\text{K}$ $\epsilon_{\text{eff}} \approx -0.40\%$



WPDIV - Technology R&D for HHF PFCs

- Study improvements of ITER technology
- Mock-up fabrication
- HHF testing reached 100 cycles up to 20 MW/m²




Thin graded Interlayer (W/Cu)



Composite pipe (W₂/Cu)


Thermal break

100th cycle




WPRM – Remote Maintenance

- Precision control of large heavy components that deform significantly under static/dynamic loads
- In-vessel work in the high radiation areas (2kGy/hr) must be minimised and ideally avoided
- Concept designs and tests for proof-of-principle cutting and welding tools developed



Multi-Module Segment Blanket Handling



- Proof of principle tool designs completed
- Fit-up tolerance and filler material methods
 - Post weld heat treatment
 - Control of weld profile with dual lasers

Keelan Keogh et al. (CCFE) to appear in Fus. Eng. Des.



In-bore weld achieved


2017 Welding Tool Proof of Principle Detailed Design

WPBB – Blanket Fabrication Technologies

WCLL (EUROFER tubes)



HIP and EB processes (FW / cooling plates)



Spark erosion and bending (FW)




Initial Industrial Involvement



- Project / Program Management
- Plant Architect Engineering: Systems Engineering and Design Integration
- Cost, risk, safety and RAMI analysis
- Evaluation and selection of design alternatives
- Plant engineering tools, modelling and simulation
- TRL assessment, etc.
- Design for robustness and manufacture of critical components/systems; include design simplification/ reduce fabrication costs

- Architect engineering studies support
- Evaluation and selection of design alternatives
- FIIF (Chairman)



- System Engineering Training
- Advisory role on Central Integration Project Team
- FIIF



Fusion Industry
Innovation Forum

- Atmosstat
- Empresarios Agrupado
- Cosylab
- Assystem
- Saarstahl, Germany
- CSM S.p.A., Rome, Italy
- Plansee
- GRS GmbH



- Design studies BOP/PCS
- Design amelioration of turbines for pulsed loads
- FIIF



Design for simplification and robustness of critical components such as vacuum vessel; reduce fabrication costs

Ongoing International Collaborations



❖ Japan (Broader Approach) IFERC

- joint DEMO Design Activities (DDA) to address most critical DEMO design issues
investigate feasible DEMO design concepts

❖ China as of 2016

- **DEMO/ CFETR joint design task forces**
 - Technical exchange meetings: CFETR and EU-DEMO
 - Systems codes studies
 - Divertor configuration and performance, incl. alternative divertor geometries and potential implementation in CFETR / EU-DEMO / DTT
- **Breeding blanket R&D cooperation:**

❖ UCLA (DCLL) + Structural Codes

- upgrade and use of existing MaPLE facility for combined magneto-hydrodynamic (MHD) thermofluids and fluid-materials interaction experiments


❖ Fission Reactor Irradiation Experiment

- Collaborations to use non-EU MTRs for high fluence irradiation to close gaps in EUROFER and Cu data base and work towards common MPH and design rule development



Main Challenges

- ✓ **Integration of design drivers across different systems**
- ✓ **High degree of complexity/ system Interdependencies**
- ✓ **Design dealing with uncertainties (physics and technology)**
- **Emphasis should be on design integration risks and engineering/operational challenges** arising from power conversion aspects and technology feasibility, safety licensability and RH
- **Postponing integration assuming that it restricts innovation and inhibits an attractive DEMO plant, risks developing design solutions that cannot be integrated in practice**
- **A lot of discussions about making fusion smaller, cheaper, and faster, but there is no magic bullet to solve the integrated design problems**
 - Every time you squeeze somewhere, you make problems worse elsewhere...
 - EU-DEMO is current viewed to be the lowest risk option to meet all targets within given timescales (this does not mean it is low risk!)
- ❖ **This approach represents an important change in the EU fusion laboratory culture**
- ❖ **Involvement of industry and exploitation of international collaborations on a number of critical areas is necessary**



Acknowledgements



The PPPT PMU Team:


C. Bachmann, S. Ciattaglia, F. Cismondi, E. Diegele, T. Franke, C. Gliss, G. Keech, R. Kembleton, F. Maviglia, B. Meszaros, M. Siccinio, C. Vorpahl, H. Walden.



The PPPT Project Leaders:

L. Boccaccini (KIT), G. Pintsuk (FZJ), C. Day (KIT), W. Biel (FZJ), J-H. You (IPP), N. Taylor (CCFE), T. Loving (CCFE), V. Corato (ENEA), A. Ibarra (CIEMAT), M.Q. Tran (CRPP), L. Barucca (Ansaldo Nucleare), C. Bustreo (Consorzio RFX).

The EU Fusion Laboratories involved:



The contents of this document cannot be reproduced without prior permission of the authors.